

**S 15**

- Brake Maintenance
- Hydraulic Devices
- Wheel Alignment
- Tyre Service
- Engineering

Order-No.: **1015**  
**1114 R**

Type: **S 15**  
**SE 14**



The **S 15/SE 14** is a solid, movable brake maintenance device with an internal 19 l tank (15 l at **SE 14**). With the help of the S 15/SE 14 hydraulic brake systems and hydraulic clutches of passenger cars, commercial vehicles and motorcycles can be maintained. The change of synthetic brake fluid is done fast and without any problems. The complete ventilation of the brake system assures the functional safety of the brake- and ABS- and SBC-systems.

The easy movement of the wheel-brake cylinder can be checked as well as a leakage test at the brake- and coupling system after repairs.

**Description:**

**Optical fill level indication** by three control lights at S 15 (except SE 14, there is an acoustic signal indicating the minimum level).

**Electrical powered pump:** After switching-on the pump the pressure builds up slowly. This prevents a „foaming“ of the brake fluid with air because of the small flow velocity.

**Automatic switch-off** of the pump when reaching the minimal capacity. Therefore no air will get into the hydraulic system. A separation of the device from the car when filling up the internal tank is not necessary, the ventilation process can be continued immediately.

**Infinitely adjustable pressure regulation** from 0.4 to 3.5 bar with manometer indication and low pressure test.

**Pulsating liquid current** of the brake fluid. These oscillations make a complete ventilation of the pipes possible, because even the smallest air- and humidity locks at the pipe walls are getting carried away.

**Automatically pressure decrease** when switching off the device. The device can be disconnected from the adapter without pressure by the quick coupling. There is no overflow of the brake fluid.

The 3.5 m long inflating hose makes the ventilation possible on every car lift without any problems.

**Simple handling**, therefore no training is necessary, uncomplicated refilling.

**Suitable for ABS- and SBC-brake systems.**

**Technical Data:**

Electrical connection: 230 V/50 Hz, optional 110 V/60 Hz or 12 V

Dimensions (LxWxH) in mm: 370 x 370 x 460

Weight: about 21.5 kg

**Order-No.:**

1015 (S 15)/1114 R (SE 14)

**Scope of delivery:**

Standard adapter 50232.

**Accessory:**

Catch bottle (50256) and adapters for almost all vehicles.

Complete disposal system for used brake fluid.

**Modifications and errors reserved, 09/01/2008**