

ROMESS®

Romess Rogg Apparate +
Electronic GmbH & Co. KG
Dickenhardtstr. 67
78054 Villingen-Schwenningen
Tel.: + 49 (0) 7720 9770 0
Fax.: + 49 (0) 7720 9770 25
romess.rogg@t-online.de
Germany



S 20 DUO

- Brake Maintenance
- Hydraulic Devices
- Wheel Alignment
- Tyre Service
- Engineering

Order-No.: **1020/1020 D**
2320/2320 D

Type: **S 20/S 20 Duo**
SE 20/SE 20 DUO



The **S 20/S 20 DUO** and the **SE 20/SE 20 DUO** are movable brake maintenance devices for the use of 5 – 20 l canisters. Therefore these devices are suitable for garages of all sizes. With the help of the **S 20/S 20 DUO** and **SE 20/SE 20 DUO** hydraulic brake systems and hydraulic clutches of passenger cars, commercial vehicles and motorcycles can be maintained. The change of synthetic brake fluid is done fast and without any problems. The complete ventilation of the brake system assures the functional safety of the brake and ABS- and with **S 20/S 20 DUO** also for SBC-systems.

The **S 20 DUO** and the **SE 20 DUO** offers the pre-draining of the brake fluid out of the brake-fluid reservoir of the vehicle.

Description:

Electrical powered pump: After switching-on the pump the pressure builds up slowly. This prevents a „foaming“ of the brake fluid with air because of the small flow velocity.

Automatic switch-off of the pump when reaching the minimal capacity. Therefore no air will get into the hydraulic system. A separation of the device when changing the containers is not necessary, the ventilation process can be continued immediately.

Infinitely adjustable pressure regulation from 0.4 to 3.5 bar at S 20/S 20 DUO and from about 0.5 to 2.0 bar (maximal 2.4 bar) at SE 20/SE 20 DUO with manometer indication.

Pulsating liquid current of the brake fluid. These oscillations make a complete ventilation of the pipes possible, because even the smallest air- and humidity locks at the pipe walls are getting carried away.

Automatically pressure decrease when switching off the device. The device can be disconnected from the adapter without pressure by the quick coupling. There is no overflow of the brake fluid.

The 3.5 m long inflating hose makes the ventilation possible on every car lift without any problems.

Simple handling, no training is necessary.

Suitable for ABS- and with S 20/S 20 DUO also for SBC-brake systems.

Technical Data:

Electrical connection: 230 V/50 Hz, optional 110 V/60 Hz or 12 V

Dimensions (LxWxH) in mm: 590 x 450 x 630

Weight: about 16.0 kg

Order-No.:

1020 (S 20)/1020 D (S 20 DUO) and 2320 (SE 20)/2322 (SE 20 DUO)

Scope of delivery:

Tank tube and adapter (cone) for 5-20 liter canisters with a bottle holder (for S 20 and SE 20 as option available) and standard adapter 50232.

Catch bottle optional for manual disposal or with adapter for SET-Schröder or ATE disposal systems for used brake fluid (S 20 Duo and SE 20 DUO only).

Accessory:

Catch bottle (50256) and adapters for almost all vehicles.

Complete disposal system for used brake fluid.

Modifications and errors reserved, 09/01/2010