



S 30-60 DUO

ROMESS®

Romess Rogg Apparate +
Electronic GmbH & Co. KG
Dickenhardtstr. 67
78054 Villingen-Schwenningen
Tel.: + 49 (0) 7720 9770 0
Fax.: + 49 (0) 7720 9770 25
romess.rogg@t-online.de
Germany

- Brake Maintenance
- Hydraulic Devices
- Wheel Alignment
- Tyre Service
- Engineering

Order-No.: **1332/1333**
1335

Type: **S 30-60/SE 30-60**
S 30-60 Duo



The **S 30-60/SE 30-60/S 30-60 DUO** is a movable brake maintenance device for the use of 30 – 60 l canisters. Therefore the device is suitable for garages of all sizes. With the help of the **S 30-60/SE 30-60/S 30-60 DUO** hydraulic brake systems and hydraulic clutches of passenger cars, commercial vehicles and motorcycles can be maintained. The change of synthetic brake-fluid is done fast and without any problems. The complete ventilation of the brake system assures the functional safety of the ABS- and SBC-systems. The easy movement of the wheel-brake cylinder can be checked as well as a leakage test at the brake- and coupling system after repairs.

The **S 30-60 DUO** offers the pre-draining of the brake fluid out of the brake-fluid reservoir of the vehicle.

Description:

Optical fill level indication by three control lights (one red control light at SE 30-60).

Electrical powered pump: After switching-on the pump the pressure builds up slowly. This prevents a „foaming“ of the brake-fluid with air because of the small flow velocity.

Automatic switch-off of the pump when reaching the minimal capacity. Therefore no air will get into the hydraulic system. A separation of the device while changing the containers is not necessary, the ventilation process can be continued immediately.

Infinitely adjustable pressure regulation from 0.4 to 3.5 bar with manometer indication and low pressure test.

Pulsating liquid current of the brake-fluid. These oscillations make a complete ventilation of the pipes possible, because even the smallest air- and humidity locks at the pipe walls are getting carried away.

Automatically pressure decrease when switching off the device. The device can be disconnected from the adapter without pressure by the quick coupling. There is no overflow of the brake fluid.

The 3.5 m long inflating hose makes the ventilation possible on every car lift without any problems.

With a **converter lockup switch (not for SE 30-60)** the remaining quantity can be pumped over a new can in case of change.

Filter (order-no. 90594) at the tank tube at the inlet side and additional for S 30-60 DUO filter at the hose for the draining (filters should be exchanged once a year or after visual control if polluted)!

Simple handling, therefore no training is necessary.

Suitable for ABS- and SBC-brake systems.

Technical Data:

Electrical connection: 230 V/50 Hz, optional 110 V/60 Hz or 12 V

Dimensions (LxWxH) in mm: 650 x 500 x 880

Weight: about 34 kg

Order-No.:

1332 (S 30-60)/1333 (SE 30-60)/1335 (S 30-60 DUO)

Scope of delivery:

Tank tube and adapter for 30-60 liter canisters with screw connector 50418, bottle holder (not for SE 30-60) and standard adapter 50232.

Catch bottle optional for manual disposal or with adapter for SET-Schröder or ATE disposal systems for used brake fluid (S 30-60 Duo only).

Accessory:

Catch bottle (50256), adapter for containers with a pull-out plastic tap (13325) and adapters for almost all vehicles.

Complete disposal system for used brake fluid.

Modifications and errors reserved, 07/01/2009