



- Brake Maintenance
- Hydraulic Devices
- Wheel Alignment
- Tyre Service
- Engineering

Order-No.: **1008 B**

Type: **SE 8 B**



The **SE 8 B** is a movable brake maintenance device for the use of 5 – 20 l canisters. Therefore the device is suitable for garages of all sizes.

With the help of the **SE 8 B** hydraulic brake systems and hydraulic clutches of passenger cars, commercial vehicles and motorcycles can be maintained. The change of synthetic brake fluid is done fast and without any problems. The complete ventilation of the brake system assures the functional safety of the brake including ABS-systems.

**Description:**

**Electrical powered pump:** After switching-on the pump the pressure builds up slowly. This prevents a „foaming“ of the brake fluid with air because of the small flow velocity.

**Automatic switch-off** of the pump when reaching the minimal capacity. Therefore no air will get into the hydraulic system.

**Infinitely adjustable pressure regulation** from 0.4 to 2.0 bar (maximal 2.4 bar) with manometer indication.

**Automatically pressure decrease** when switching off the device. The device can be disconnected from the adapter without pressure by the quick coupling. There is no overflow of the brake fluid.

The 3.5 m long inflating hose makes the ventilation possible on every car lift without any problems.

**Simple handling**, therefore no training is necessary.

**Suitable for ABS- systems.**

**Technical Data:**

Electrical connection: 230 V/50 Hz, optional 110 V/60 Hz or 12 V

Dimensions (LxWxH) in mm: 380 x 420 x 800

Weight: about 10.0 kg

**Scope of delivery:**

Tank tube and adapter (cone) for 5-20 liter canisters and standard adapter 50232.

**Order-No.:**

1008 B

**Accessory:**

Catch bottle (50256) and adapters for almost all vehicles.

Complete disposal system for used brake fluid.

**Modifications and errors reserved, 09/01/2008**